

Laminated Insulations & Plastics Ltd.

Tel: +44 (0) 1246 475077 Adelphi Way Fax: +44 (0) 1246 474439
Ireland Industrial Estate
Staveley
Derbyshire
S43 3LS

Technical Data Sheet

SRBF Grade F2

Fine weave high quality fabric grade combines excellent mechanical strength with first class electrical properties and low water absorption. Thermal class "E".

Physical Properties		Unit	Value
Cross Breaking strength		MPa	130
Impact strength, notched charpy		kJ/ m ²	11.5
Compressive strength	Flat wise	MPa	310
	Edge wise	MPa	200
Resistance to flat wise compression			1.5
Shear strength, flat wise		MPa	90
Water absorption	1.6mm	MG	90
Electrical strength in oil @ 90°C	1.6mm	%	4.5
	3.0mm	MV/m	2.6
	6.0mm		2.0
Electrical strength edgeways in oil @ 90°C		kV	12
Insulation resistance after immersion in water		M.ohms	10 ³
Comparative tracking index		V	110
Relative Density			1.36
Maximum working temperature	Continuous	°C	120
	Intermittent	°C	130
Standard sheet size			1.2m x 1.2m
Standard thickness range		mm	0.8 - 150
Colour: Golden			
Specification to BS 2572			

These are typical average values and do not constitute a specification. It is the responsibility of the customer to assess the suitability of the product for use.